

WS-C3750G-24PS-S Datasheet

Get a Quote



Overview

Cisco Catalyst 3750G-24PS Power over ethernet switch is an innovative switch that improves LAN operating efficiency by combining industry-leading ease of use and the highest resiliency available for stackable switches. This product series represents the next generation in desktop switches, and features Cisco StackWise technology, a 32-Gbps stack interconnect that allows customers to build a unified, highly resilient switching system one switch at a time

- 24 Ethernet 10/100/1000 ports with IEEE 802.3af and Cisco prestandard PoE
- 4 SFP-based Gigabit Ethernet ports
- 32-Gbps, high-speed stacking bus
- Innovative stacking technology
- 1 RU stackable, multilayer switch
- Enterprise-class intelligent services delivered to the network edge
- IP Base software feature set (IPB)

Specification

WS-C3750G-24PS-S data sheet	
Manufacturer	Cisco Systems, Inc
Manufacturer Part Number	WS-C3750G-24PS-S
Product Type	Managed, Stackable 24 ports L3 Switch
Form Factor	Fixed, Rack Mountable 1U, Stackable/Clustering
Switch Port density - Uplinks	24 x 10/100/1000 Ethernet Ports + 4 x SFP
Power Over Ethernet (PoE)	Yes
Performance	Switching capacity : 32 Gbps Forwarding performance : 38.7 mpps
MAC Address Table Size	12K entries
Jumbo Frame Support	Yes
Max Number of Stacks	9
Routing Protocol	RIP-1, RIP-2, HSRP, static IP routing, RIPng
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, SSH, CLI
Authentication Method	Kerberos, Secure Shell (SSH), RADIUS, TACACS+

Features	Flow control, full duplex capability, Layer 3 switching, auto-sensing per device, IP-routing, DHCP support, power over Ethernet (PoE), auto-negotiation, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, traffic shaping, stackable, Spanning Tree Protocol (STP) support, Rapid Spanning Tree Protocol (RSTP) support, Multiple Spanning Tree Protocol (MSTP) support, Dynamic Trunking Protocol (DTP) support, Port Aggregation Protocol (PAgP) support, Trivial File Transfer Protocol (TFTP) support, Access Control List (ACL) support, Quality of Service (QoS), RADIUS support, Jumbo Frames support, Cisco StackWise Technology, Cisco EnergyWise technology, Uni-Directional Link Detection (UDLD), Rapid Per-VLAN Spanning Tree Plus (PVRST+), Link Aggregation Control Protocol (LACP), Remote Switch Port Analyzer (RSPAN)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s
DRAM Memory	128 MB
Flash Memory	32 MB Flash
LED Status Lights Indicators	Link activity, port transmission speed, port duplex mode, bandwidth utilization %, system, RPS (Redundant Power Supply)
Connectivity / Expansion Slots	
Interfaces	24 x 10Base-T/100Base-TX/1000Base-T - RJ-45 - PoE 1 x console - RJ-45 - management Network stack device : 1 x x 2 4 x SFP (mini-GBIC)
Power Supply Specifications	
Power Device	Power supply - internal
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	540 Watt
Features	Redundant Power System (RPS) connector
Dimensions / Weight / Miscellaneous	
Width	44.5 cm
Depth	37.8 cm
Height	4.4 cm
Weight	6.1 kg
MTBF	182,373 hour(s)
Compliant Standards	CE, FCC Class A certified, TUV GS, BSMI CNS 13438 Class A, CISPR 24, cUL, EN 60950, EN55022, NOM, VCCI Class A ITE, IEC 60950, EN55024, UL 60950 Third Edition, CISPR 22, CSA 22.2 No. 60950, CB, FCC Part 15, MIC, AS/NZS 3548
System Software	
Software Included	Cisco IOS IP Base
Manufacturer Warranty	
Service & Support	Limited lifetime warranty
Service & Support Details	Limited warranty - lifetime

Want to Buy

- Order Now
- Get a Quote

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com