



2021-Q2

2 years Silver Guarantee

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

سایر برتری‌ها:

- پشتیبانی از میکرو SD با ظرفیت 128GB
- بدنه ضد آب و گرد و غبار با درجه IP67
- سرور انتقال تصویر در ایران
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.4
- قابلیت WDR, BLC, HLC, Defog

قابلیت‌های هوشمند:

- عبور از خط
- فنس مجازی
- ورود به منطقه
- خروج از منطقه
- گم شدن اشیاء
- اضافه شدن اشیاء
- تشخیص چهره
- تشخیص حرکت
- تشخیص رنگ
- تشخیص روشنایی
- تشخیص کنتراست
- تشخیص تغییر زاویه دوربین
- تشخیص صدای غیر عادی
- تشخیص تغییر فکوس لنز
- ردیابی هوشمند

Camera	
Image Sensor	2MP Starlight (Sony-Japan) Cmos Sensor (1/2.8")
Case Size	8"
CPU	Dual-Core ARM Cortex-A7@900MHz
Lens	33X Optical Lens (4.7~155mm)- DIS
Resolution	1920*1080 (2MP)
Available IR Range	150~200M Smart IR SMD Technology
D/N Filter	IR Cut Filter Switch (ICR)
Min Illumination	Color: 0.01 Lux(AGC on) - B/W: 0.0 Lux(IR on)
PTZ	Pan Range: 360° Endless - Pan Speed: 0.1~240°/S Tilt Range: -10°~100° - Tilt Speed: 0.1~180°/S Number of Preset: 255 - Patrol: 4 - Pattern: 8 - Park Action: Yes
StarLight View	Yes-Color
Picture Adjust	
Picture Function	120db WDR, DWDR, BLC, HLC, Defog, ROI
Shutter Speed	Manual (1/3 ~ 1/100.000), Auto
Image Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Setting	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264+(Ultra H.264), H.265+ (Ultra H.265)
Audio Compression	G.711A, G.711U
Frame Rate(60Hz)	30fps@1080P (WDR ON)
Transmission Stream	Triple Stream (Code Rate: 128kb-16mb)
Network	
Protocols	HTTPs, HTTP, TCP/IP V4-V6, ICMP, RTSP, UDP, NTP, DHCP, DDNS, FTP, SNMP-V1-V2-V3, UPNP, SIP, NAT
Compatibility	Onvif Ver2.4, Profile S, CGI, SDK, API
Streaming Method	Unicast
Web Viewer	Internet Explorer
Recording Software	Unlimited KDT CMS 128CH Per Monitor

Function	
Recording	FTP, NVR, CMS, NAS, SD Card
Record Type	Manual, Motion Detection, Smart Detection, Schedule
Alarm Triggers	All Intelligent Function
Event Action	Email, Snapshot, Recording, Alarm Out
Intelligent Function	15 Smart Function Line Crossing, Virtual Fence, Entering The Area, Leaving The Area, Loss Of Objects, Added Objects, Face Detection, Color Detection, Brightness Detection, Contrast Detection, Scene Change Detection, Blurred Detection, Audio Exception Detection, Tracking Detection, Motion Detection
Interface	
Network	RJ45(10/100Mbps)+LED Indicator on Cable
Audio	Audio Out, Audio In
Alarm	Alarm Out, Alarm In
CVBS	N/A
Power	High PoE LAN, DC/AC In
Control	N/A
Memory Slot	Yes - Micro SD (128Gb Max)
General	
IP Rating	IP67, IK10, 3KV Surge Protection
Power Supply	AC24V ± 25%
POE Supply	IEEE802.3at-Max 57W(1.18A)
Web Language	English, Persian
Dimension	227*336 mm
Weight	6.5 kg
Operation Humidity	Max Up to 95%RH(Non Condensing)
Operation Temp	-40°C ~ +70°C
Silver	
Product Warranty	2 Years Silver Guarantee
MTBF	100K hrs min. MIL-HDBK-217F (25°)