

4MP Fixed-focal Wi-Fi Turret Network Camera

DH-T4A-PV



Series Overview

The Turret Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. They capture sharp, detailed images of scenes in high definition and offer powerful functions, such as AI human detection, to accurately trigger alarms. Information is also synchronously sent to your phone to keep you up-to-date. With its IP67 rating, these cameras are able to withstand harsh environments, making them highly suitable for use in small and medium-sized settings such as small-sized retail stores.



4MP Clear images with sharp details



Sound and Light Alarm Provides instant alarms to deter intruders



H.265 Advanced H.265 compression technology



Al Human Detection Focuses on what matters and reduces false alarms



Two-way Talk Communication anytime, anywhere



DMSS App Easy to use



Smart Dual Light Captures color details for post-event review



IP67 Protection Withstands harsh environments



Micro SD Card Low-cost storage



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.







Specifications

Camera

Camera			
		Smart Illumination	Yes
Image Sensor	1/3" CMOS	Image Rotation	0°/180°
Max. Resolution	2560 (H) × 1440 (V)	Built-in MIC	Yes, built-in Mic
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s	Built-in Speaker	Yes
Illumination Distance	Up to 30 m (98.53 ft) (IR)	Audio Compression	G.711a; G.711Mu; PCM; G.726
	Up to 30 m (98.53 ft) (Warm light)	Network	
Illuminator On/Off Control	Auto	Network Port	RJ-45 (10/100 Base-T)
Illuminator Number	1 (IR LED); 1 (Warm light)	Wi-Fi	IEEE802.11b/g/n 2.4–2.4835 GHz; 2.4 G
Max. Aperture	F1.6	Storage	Micro SD card (support max. 256 GB)
Field of View	2.8 mm: H: 98°; V: 55°; D: 115° 3.6 mm: H: 78°; V: 41°; D: 94°	Management Software	Smart PSS; DSS; DMSS
1.1.10	5.6 mm. n. 76 , 0. 41 , 0. 54	Mobile Client	iOS;Android
Intelligence		General	
Human Detection Video & Audio	Support the classification and accurate detection of human	Certifications	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; CE-RED: Radio Equipment Directive 2014/53/EU
Video Compression	H.264B; H.264; H.264H; H.265	Power Supply	12 VDC
Video Frame Rate	Main stream: 2560 × 1440@(1–25/30 fps); sub stream: 640 × 480@(1–25/30 fps); *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.	Power Consumption	Basic: 2.2 W (12 VDC) Max. (H.265+ illuminator intensity): 7.1 W (12 VDC)
		Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Resolution	4M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720)	Operating Humidity	≤95%
		Protection	IP67
Video Bit Rate	H.264: 32kbps ~ 4096kbps H.265: 12kbps ~ 4096kbps	Casing Material	Inner core: Metal + Plastic; Cover: Plastic
Day/Night	Auto(ICR)/Color/B/W	Cover: Plastic	Ф109.9 mm × 102.2 mm (Ø4.33" × 4.02")
Motion Detection	OFF/ON	Net Weight	353 g (0.78 lb)
Region of Interest (RoI)	Yes		0 \ 10/

What's in the box



Tools: Installation Position Map×1 Mounting Plate×1 Screw Package×1 Waterproof Connector x 1

Documents:

QR Code×1 Quick Start Guide×1 Legal and Regulation Information×1

Power:

Power Adapter×1